

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification: G01K 3/04		A1	(11) International Publication Number: WO 99/36755
			(43) International Publication Date: 22 July 1999 (22.07.99)
(21) International Application Number: PCT/GB99/00044		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 18 January 1999 (18.01.99)		Published With international search report	
(30) Priority Data: 9800814 7 16 January 1998 (16.01.98) GB			
(71) Applicant for all designated States except (US): FOOD GUARDIAN LIMITED (GB/GB); Ashfields, Leigh Sinton, Malvern, Worcestershire WR15 5DH (GB).			
(72) Inventors; and (73) Inventors/Applicants (for US only): MOULE, Robert (GB GB), Chygumo Lannorna, Penzance TR19 6XH (GB); MOULE, Simon (GB/GB), 42 Endymion Road, London N4 1EQ (GB).			
(74) Agents: ATKINSON, Peter, Birch: Marks & Clerk, Sussex House, 53-85 Mosley Street, Manchester M2 3LG (GB).			
(54) Title: BARRIER MATERIALS AND PRODUCTS PRODUCED THEREWITH			
(57) Abstract			
<p>A marking element (1) for indicating whether a pre-defined temperature condition has been maintained. The element comprises a first material (7) capable of flowing above a predetermined temperature separated from a second absorbent material (5, 10) by a heat disruptable barrier layer (4). The first and second materials are such that when the barrier layer is punctured and the predetermined temperature is exceeded the first material flows in the second material to produce a detectable change. The heat disruptable barrier layer (4) is comprised of a heat disruptable material (8) associated with an element (9) capable of being inductively heated by electromagnetic energy to effect disruption of said material thereby to activate the marking element.</p>			

BEST AVAILABLE COPY

00500359 000401